

Hisense
OFFICIAL PARTNER



Aeolus Fixed Speed



OF
YOUR
HOME



AI Smart



Ceiling & Floor
Airflow



Fast
Cooling



Wi-Fi
Control



Super Quiet
Mode



150V Low Voltage
Operation



Self-Diagnosis
Protection



-25°C Heating



8°C Heating



Non-Inverter Type		AS-09HW4SYRCK00 Heat pump	AS-12HW4SVRCK04 Heat pump	AS-18HW4SXSCCK01 Heat pump	AS-22HW4SBTCK00 Heat pump
RATINGS					
Cooling Capacity	W	2500	3200	5000	6100
Heating Capacity	W	2600	3300	5200	6250
Power Input-Cooling	W	810	1050	1625	2000
Power Input-Heating	W	695	960	1510	1825
Moisture Removal	L/H.r	-	-	-	-
Air Circulation	CMH Max	600	580	950	1100
EER for Cooling	W/W	3.09	3.05	3.08	3.05
COP for Heating	W/W	3.74	3.44	3.44	3.42
Energy Consumption	kWh / year	405	525	812.5	1000
Energy Class for Argentina	Cooling	B	B	B	A
Energy Class for Argentina	Heating	A++	A+	A+	A+
Refrigerant		R410A	R410A	R410A	R410A
Refrigerant Volume	g	620	700	1250	1430
Indoor Unit Noise Level	High (dB (A))	38	39	43	45
	Low (dB (A))	-	-	-	-
Outdoor Unit Noise Level	dB (A)	51	53	54	57
POWER SUPPLY					
Voltage, Frequency, Phase		220-240V~,50Hz,1P	220-240V~,50Hz,1P	220-240V~,50Hz,1P	220-240V/50Hz
Rated Current	Cooling (A)	3,8	5,1	7,3	8,9
	Heating (A)	3,3	4,7	6,8	8,2
LRA	A	20	25	41	45
CONNECTING PIPE DIAMETER					
Liquid Pipe	inch	1/4	1/4	1/4	3/8
Gas Pipe	inch	3/8	3/8	1/2	5/8
Maximum Connection Pipe Length	m	15	15	15	15
Maximum Height Difference	m	5	5	5	5
OTHER (VQ PANEL)					
Net Dimensions WxHxD (mm)	Indoor Unit	790x197x255	790x197x255	890x220x300	998x225x325
	Outdoor Unit	660x482x240	715x482x240	810x585x280	860x650x310
Net Weight (kg)	Indoor Unit	7,5	7,5	10	12,5
	Outdoor Unit	25	26	41	42,5
Packing Dimensions WxHxD (mm)	Indoor Unit	850x260x320	850x260x320	960x300x365	1060x315x390
	Outdoor Unit	780x530x345	830x530x345	940x630x385	995x720x420
Gross Weight (kg)	Indoor Unit	9	9	12	15
	Outdoor Unit	27	28,5	45	46,5
Loading Capacity (20'/40'/40'HC) without Pipe		146/298/339	140/278/322	88/182/208	62/128/145

